

KIOS 7 (KI-60578)



Product description


With recessing box / driver - Flat frame - RGBW



Luminaire structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- 5.5 mm thick front ring ingrade 316 stainless steel
- Single cable entry, through wiring upon request
- Supplied with 500mm power cable, 500mm DMX Input and 500mm DMX Output cables. IP Connectors not included
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency PMMA lens
- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for drive-over with a maximum load of 2000 kg
- Vehicles with pneumatic tyres can drive over the luminaire but the speed must not exceed 50 km/h
- Load is transferred by the housing to the foundation
- The distance between the floodlight and the illuminated surface should be at least 0.5 m

Light symbol



Product colour



Technical information

Light source	7 LED
Light source type	LED
Dimming type	DMX,DMX/RDM
Material	Stainless Steel
Weight	6.5 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	29 W
Lumen	1063 - 1299 lm
Efficacy	37 - 45 lm/W
CCT / CRI	RGBW30, RGBW40
Drive current	350 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	E [26°x 48°], N [21°], M [35°]
Bug	B0-U5-G0
ULR	100%
ULOR	100%

Product variants

HOW TO SPECIFY

LIGA	-	KI-60578	-	350	-	M	-	RGBW30	-	DMX/RDM	-	00
		MODEL		OUTPUT		DISTRIBUTION		CRI/CCT		DIMMING		COLOUR FINISH
		KI-60578		350 29W		E		RGBW30		DMX		00 STAINLESS STEEL
						N		RGBW40		DMX/RDM		
						M						

