

RADO 5 (RA-40582)



Product description

With recessing box



Luminaire structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear

Light symbol



G

Product colour




01-Black (RAL 9011)    02-Dark Grey (RAL 7043)    03-White (RAL 9003)    05-Matt Silver (RAL 9006)



06-Bronze (RAL 6014)

Special finishes upon request




SU01-Concrete Urban    SU02-Softscape Urban    SU03-Stone Urban    SU04-Corten Urban



SW01-OAK Woodland



SW02-Walnut Woodland



SW03-PINE Woodland

Technical information

Light source	4 x 12 LED
Light source type	LED
Dimming type	DALI, On/Off
Material	Aluminium
Weight	1.4 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	17 W
Lumen	402 - 447 lm
Efficacy	24 - 26 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	350 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz




Optic	G [32°x88°]
Bug	B0-U2-G1
ULR	7%
ULOR	7%
CIE flux code n°3	82
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hrs)	23,000
Lifetime L80B10 (hrs)	45,000
Lifetime L80B50 (hrs)	49,000

RADO 5 (RA-40582)

Product variants

HOW TO SPECIFY

LIGA	-	RA-40582	-	350	-	G	-	8030	-	ND	-	01
		<b>MODEL</b>		<b>OUTPUT</b>		<b>DISTRIBUTION</b>		<b>CRI/CCT</b>		<b>DIMMING</b>		<b>COLOUR FINISH</b>
		RA-40582		350 17W		G		8030		ND		01 BLACK
								8040		DALI		02 DARK GREY
												03 WHITE
												05 MATT SILVER
												06 BRONZE
												S - SPECIAL FINISH



RECESSING BOX