


**LIGHTALK 7 (LA-30013)**



**Product description**


With driver - Constant current (CC)  
500 mA - 610 mm - Class I - RGBW




**Luminaire structure**

- Die-cast aluminium end-caps
- Extruded aluminium housing and sheet aluminium front frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Four IP68 connectors supplied with 2x0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable for LA-30013
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear

**Light symbol**



E M N VN



W

**Product colour**



01-Black (RAL 9011) 02-Dark Grey (RAL 7043) 03-White (RAL 9003) 05-Matt Silver (RAL 9006)



06-Bronze (RAL 6014)

**Special finishes upon request**



SU01-Concrete Urban SU02-Softscape Urban SU03-Stone Urban SU04-Corten Urban



SW01-OAK Woodland SW02-Walnut Woodland SW03-PINE Woodland

**Technical information**

Light source	20 LED
Light source type	LED
Dimming type	DMX, DMX/RDM
Material	Aluminium
Weight	3.8 kg
Operating temperature	-20°C to 40°C

<b>Luminaire</b>	
Power	33 W
Lumen	1677 - 2018 lm
Efficacy	51 - 61 lm/W
CCT / CRI	RGBW30, RGBW40
Drive current	500 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	E [16° x 35°], M [24°], N [13°], VN [10°], W [43°]
MacAdam Ellipse	7 SDCM
Lifetime L90B10 (hrs)	50,000
Lifetime L80B10 (hrs)	68,000
Lifetime L80B50 (hrs)	100,000

Product variants

HOW TO SPECIFY

LIGA - LA-30013 - 500 - M - RGBW30 - DMX/RDM - 01						
MODEL	OUTPUT	DISTRIBUTION	CRI/CCT	DIMMING	COLOUR FINISH	
LA-30013	500 33W	E	RGBW30	DMX	01 BLACK	
		M	RGBW40	DMX/RDM	02 DARK GREY	
		N			03 WHITE	
		VN			05 MATT SILVER	
		W			06 BRONZE	
						S - SPECIAL FINISH

