

QUARTER 1 (QU-31392)



IP65

IK08

Product description

Small



microVos™
TECHNOLOGY



Luminaire structure

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear

Light symbol



EW M T1 T2



T3 T4 W LA01

Product colour



01-Black (RAL 9011) 02-Dark Grey (RAL 7043) 03-White (RAL 9003) 05-Matt Silver (RAL 9006)



06-Bronze (RAL 6014)

Special finishes upon request



SU01-Concrete Urban SU02-Softscape Urban SU03-Stone Urban SU04-Corten Urban



SW01-OAK Woodland SW02-Walnut Woodland SW03-PINE Woodland

Technical information

Light source	24 LED
Light source type	LED
Dimming type	DALI, On/Off
Material	Aluminium
Weight	6.0 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	53 W
Lumen	6244 - 7178 lm
Efficacy	118 - 135 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	700 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	EW [112°], M [31°], T1 [145° x 75°], T2 [137° x 58°], T3 [123° x 92°], T4 [105° x 69°], W [56°], LA01 [133° x 56°]
Bug	B2-U0-G0, B3-U0-G1, B1-U0-G1, B3-U0-G3, B2-U0-G2, B3-U0-G0
ULR	0%
ULOR	0%
CIE flux code n°3	99, 97, 96, 98
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hrs)	> 90,000
Lifetime L80B10 (hrs)	> 90,000
Lifetime L80B50 (hrs)	> 90,000

QUARTER 1 (QU-31392)

Product variants

HOW TO SPECIFY

LIGA	-	QU-31392	-	700	-	T2	-	8030	-	ND	-	01
MODEL	OUTPUT	DISTRIBUTION	CRI/CCT	DIMMING	COLOUR FINISH							
QU-31392	700 53W	EW	8030	ND	01 BLACK							
		M	8040	DALI	02 DARK GREY							
		T1			03 WHITE							
		T2			05 MATT SILVER							
		T3			06 BRONZE							
		T4			S - SPECIAL FINISH							
		W										
		LA01										

