

SANDY 8 (SA-31542)



Product description

Large



Luminaire structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light symbol



0

Product colour



01- Black (RAL 9011) 02- Dark Grey (RAL 7043) 03- White (RAL 9003) 05- Matt Silver (RAL 9006)



06- Bronze (RAL 6014)

Special finishes upon request



SU01- Concrete Urban SU02- Softscape Urban SU03- Stone Urban SU04- Corten Urban



SW01- OAK Woodland



SW02- Walnut Woodland



SW03- PINE Woodland

Technical information

Light source	50 LED
Light source type	LED
Dimming type	DALI, On/Off
Material	Aluminium
Weight	3.8 kg
Operating temperature	-20°C to 40°C

Luminaire	
Power	23 W
Lumen	2156 - 2156 lm
Efficacy	89 - 94 lm/W
CCT / CRI	3000K CRI80, 4000K CRI80
Drive current	700 mA
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz


Optic	0 [115°x114°]
Bug	B0-U2-G1
ULR	3%
ULOR	3%
CIE flux code n°3	92

SANDY 8 (SA-31542)

Product variants

HOW TO SPECIFY

LIGA	- SA-31542	- 700	- 8030	- ND	- 01
	MODEL	OUTPUT	CRI/CCT	DIMMING	COLOUR FINISH
	SA-31542	700 27W	8030	ND	01 BLACK
			8040	DALI	02 DARK GREY
					03 WHITE
					05 MATT SILVER
					06 BRONZE
					S - SPECIAL FINISH



Accessories



Surface mounting box for easy cabling (SANDY 8)
LIGA-SCE-SANDY-8